

www.saintyco.com

# CM-120

### Horizontal & Intermittent Cartoning Machine











#### CM-120 Cartoning Machine





## **CM-120**

The **CM-120** cartoning machine is Al-plastics blister medicine cards, injection tray, bottles, ointments, rectangular or pill articles.

Automatic folding ( 1~4 folding ) and conveying of manual leaflet, automatic material categorizing and feeding; automatic paper carton spreading, automatic manual leaflet and material carton packaging, synchronous (3-row) batch number printing, automatic paper carton sealing, automatic waster eliminating.





#### CM-120 Cartoning Machine



#### **Features:**

- Adopts full servo system, synchronous belt driving without any lubricating oil.
- > Servo motor works in feeding materials and carton packaging. Speed and travel are adjustable, stable and reliable in operation.
- Single motor driving, PLC automatic control, Operating on touch screen, words and numeric display, automatic counting and automatic speed regulation, easy to operate, stable in operation.
- Photoelectric detection and monitoring system to realize overload protection, words indication of failure diagnosis, and automatic halt of failure.
- ➤ In a specified range, realizes carton packaging of various specifications without replacing parts. And it is easy and convenient to adjust.
- > The especial designed feeding mechanism can realize sole machine produce.
- Innovative and transparent security casters to enhance general view and security of the machine.

Main tachnical parameters	CM-120
Main technical parameters	
Paper carton size: (L×W×H)	$(70\sim130) \times (45\sim100) \times (15\sim50) \text{ mm}$
Material	$250{\sim}350~g/m^2$
Manual leaflet size	(L×W) before folding: $(100\sim250)\times(100\sim150)$
	mm
	(L×W) after folding: $(100\sim150) \times (20\sim40)$
	mm
Material	$50{\sim}70~\mathrm{g/m^2}$
Clean compressed air	Pressure $0.5{\sim}0.8$ Mpa;
Air consumption (Air	>0.2 m <sup>3</sup> / min
compressor)	≥0.2 m³/ min
Power consumption	380V 50 Hz 6Kw
Vacuum source	degree of vacuum-0.09 Mpa
Dimensions (L×W×H)	4700×1100×1950 (mm)
Weight	3500Kg
Output	60~140 cartons/min
Finished product rate	≥99%
Eliminating rate of waster	100%
Working noise	≤80dB (A)

## **SaintyCo Also Offer:**

- Softgel Manufacturing Line
- Capsule Printer
- Capsule Counting Line
- Blister Packing Solutions
- Pouch Packaging Machine

For additional information, please drop E-mail to info@saintyco.com

