

Vertical Granular Packing Machine DXD-350K/500K/900K



This machine is suitable for packing any kinds of Granular and powder. Most commonly used in the pharmacy, food, dairy, and agriculture industries.

Features

1. Back sealing, three-side sealing, and four-side sealing packing method
2. The packing data and adjustment can be displayed on the screen. The user can directly operate it on it.
3. Equipped with a photoelectric controller to ensure that its packing bag patterns are perfect.
4. It can automatically finish making-bag, metering, filling, sealing, cutting, counting and printing batch number.
5. The body and the parts touching the material are made of stainless steel.

Technical Parameter

Items / Model	DXD-350K	DXD-500K	DXD-900K
Pouch length	50-250mm(L)	50~160mm	50~120mm
Pouch width	50-85mm(W)	50~105mm	50~105mm
Packing speed	30-50times/min depend on pouch size and material	20~50times/nim (depend on pouch size and material)	80times/nim (depend on pouch size & material)
Measuring range	1-50ml	1~80ml	1~80ml
Applicable film	PET/AL/PE PET/PE NY/AL/PE NY/PE	PET/AL/PE PET/PE NY/AL/PE NY/PE	PET/AL/PE PET/PE NY/AL/PE NY/PE
Max width of film roll	350mm	500mm	900mm
Max film roll diameter	300mm	420mm	300mm
Film roll core diameter	75mm	75mm	75mm
Power voltage	220V/ 50HZ	380V50Hz 3P 4W	380V 50Hz
Power	5.5kw	12 Kw	12 Kw
Gross Weight	650kg	1200kg	1200kg
Package size	1400×1000×1700mm	1680×1280×2050mm	1500×1540×2200mm