KENO-P250 Automatic Pillow Packing Machine



Main characteristic:

- 1. Be controlled by double transducer, flexible cutting and setting of bag length, time and film savable.
- 2. Human-machine operation, convenient and quick parameter setting.
- 3. Self diagnosis of failure function, clear failure display.
- 4. High sensitivity photoelectric eye tracking color mark and digital input of cut position make the sealing and cutting more accurate.
- 5. Separate PID control temperature, suitable for various packing materials.
- 6. Stopping the machine in the selected position, no sticking to the knife and no waste packing film.
- 7. Simple driving system, reliable working and convenient maintenance.
- 8. All the controls are achieved by software, convenient for function adjusting and upgrading.

Application:

Suitable for packaging soft, strip and unorganized objects like towels, tissues, noodles, egg rolls, sausages, sleeve-fish, popsicle, soft candies, biscuits, fresh fruits etc.

Performance parameter

Film width	Max.250mm
Bag length	65~190mm or 120~280mm
Bag width	30~110mm
Product heigh	Max. 40mm
Film roll diameter	Max.320mm
Packing speed	40~230 bag/min
Power supply	220V,50/60HZ,2.4KVA
Machine size	(L)3770x(W)670x(H)1450
Machine weigh	800Kg