

Stand up Pouch Filling and Sealing Machine RZ8-200D



Application

1. Solid: leisure food (candy chocolate) etc.
2. Grain: condiment (monosodium glutamate, chicken essence, granulated sugar) dry fruit (nuts), capsule, grain medicine, seed, feed etc.
3. Powder: condiment, monosodium glutamate, salt, glucose, narrowly sugar, milk powder, washing powder etc.
4. Liquid: yellow wine, soy sauce, rice juice, drink, detergent etc.
5. Thick liquid: ketchup, peanut butter, sauce, chill sauce, bean butter etc.

Bag Type

Standup bag, Doypack.

Features

- 1) Wide applications : various shapes, state and nature of products (such as rice, coarse grains, nuts, spicy snack, Chinese chestnut liquid, etc.)
- 2) Easy to operate: PLC controller, HMI system makes easy operation.
- 3) Easy to adjust: Synchronously adjust machine clamp, and parameters for different products can be saved and available from database when changing products.
- 4) High Automation: Complete all actions by grooved clamp, which is more durable than end cam, and it do not need springs to return, more stable in running.
- 5) Perfect Prevention System: when the bag is not open or not opened enough, it will be non-filling and non-sealing, so the empty bags return to the first station to refill and not wasted and it will save the production cost.
- 6) Stainless steel/other materials ensure sanitation and safety, meet the GMP standard.
- 7) Oil-free vacuum pump: avoid production environment pollution.
- 8) Waterproof Design: direct water-washing the machine surface, easy to clean, prolong the useful life.

9) Premade bag packing: high sealing quality, upgrade the finished product.
10) Adopt concentrated oil-supplied lubrication device inside the grooved cam.
(Machine clamps are adjusted in one time, mechanical actions are controlled by grooved cam, empty bag cycling, product parameters can be saved)

Technical Parameters

Model	RZ8-200D
Bag Size	W:70~200mm L:100~300mm
Filling Range	5~1500g
Packing Speed	20~50 Bags/min
Weight	1200kg
Dimension	1570mm*1440mm*1480mm(L,W,H)
Total power	3kw