

## Aerating Band Sealer FRMQ-980III



FRMQ-980III industrial grade band sealers are ideal for sealing thermoplastic materials (PP, PE, laminates) of any size and length. It allows Preferred Pack sealers to be used in a wide range of applications and industries. Gas Blower used to wind blowing into the plastic packaging, so food is not easily destroyed as packing a snack.

- Can choose stainless steel construction or Paint construction
- Adjustable speed conveyor to accommodate materials varying in thickness
- Digital temperature control (0-572 deg F) (0-300 deg C)
- Sealing speed of up to 472 inches per minute (depending on the operator, ~20-26 bags/minute)
- Maximum seal width - 10mm
- Each band sealer comes with a tool box containing easy worn spare parts.
- Easy to operate. Turn on the power and heat switch of your band sealer. When the preset temperature has been reached, place the bag in the positioning plate. The sealing band carries the bag forward and seals the bag instantly. No pushing or pulling is required.

### Parameters:

Model	FRMQ-980III
Voltage (V/Hz)	AC 220/50 110/60
Suction Pump Power(W)	185
Moter Power (W)	50
Sealing Power (W)	300×2
Printing Heating Power (W)	40×2
Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Solid-Ink Roller

Distance from Sealing Center to Conveyor Table (mm)	20-40
Conveyor Table Size (L × W) (mm)	954×153
Overall Conveyor Loading (kg)	≤3
External Dimensions (L × W × H) (mm)	1050×900×900
Net Weight (kg)	50