



FL-7555TB+SM-5030 Manual L bar Combo Sealing and Shrink Machine



Suitable for the packing demands of the mass production in industries such like electronics, hardware, plastic, software, food, printing, pharmaceuticals, floors and other construction materials.

Applicable films: PVC/POF.

Manual L Bar Sealer Technical Features:

- Teflon coated sealing wires in glass-fiber slots, making the seam straight, closed and unburnt.
- Miscalculation and overheating protection devices can effectively protect the products and the operator.
- Tailored perforators to fully evacuate the air from the film bags.
- FL-5545TB/7555TB cut and seal by cylinder, saving physical strength while improving the efficiency.

Shrink Tunnel Technical Features:

- Stainless heating tubes and strong blowing motor ensure high heating efficiency, large air volume and uniform air circulation.
- Solid metal rods wrapped by heat-resistance silicone tubes make the Conveyor rollers strong and resilient.

Dimensions:

Model	FL-7555TB	SM-5030
Machine Dimensions (mm)	1800 X 842 X 1029	1662 X 806 X 1515
Max Packing Size (mm) L+H(mm) H<200	≤700	1000 X 400 X 250
Max Packing Size (mm) W+H(mm) H<200	≤500	
Max Sealing Size (mm)	750 X 550	/
Capacity (pcs/h)	800~1200	0~15 m/min
N.W. (kg)	160	360
Power (kw)	01.май	12
Power Source	PH 220V 50/60Hz	3PH 220V/380V 50/60Hz
Air Source (kg/cm ²)	6~8	/
Applicable Film	POF/PVC	POF/PVC