

# Multi Lane Powder Stick Bag Packing Machine GH280BF / GH560BF



## Feature:

1. Famous brand PLC control, system, large touch screen, convenient to operate;
2. Advanced design, high precision and fast speed;
3. No film alarm, saving materials and no waste film;
4. Photocell tracking system for precise bag length and position of film
5. Each auger is control by servo motor, which will be more precious filling volume



**Parameter:**

<b>Model</b>	<b>GH280BF</b>	<b>GH560BF</b>
Lanes number	4-6 lane	4-10 lanes
Capacity	Max.35bags/min/lane	Max.35bags/min/lane
Measuring method	1~ 50ml	1~ 50ml
Measuring Accuracy	±2%	±2%
Measure Model	Each Lane Each Auger Filler by Servo Motor	
Bag size	L:70-120MM	L:70-120MM
	W:17-40MM	W:17-85MM
Sealing type	Back sealing/stick bag	Back sealing/stick bag
Film width	Max.280mm	Max.560mm
Film thickness	Laminated film thickness:0.07--0.10mm	
Cutting type	1.Flat Cutting; 2.Zigzag cutting; 3.Continuous cutting;	
	4.Round cutting; 5.Customized special shape cutting	
Control system	PLC+Servo+Touch screen	PPLC+Servo+Touch screen
Air consumption	0.8 MPA 0.6M3/MIN	0.8 MPA 0.6M3/MIN
Power Supply	3.5KW, 1N+PE/50HZ/AC220V	5KW, 1N+PE/50HZ/AC220V
Dimension	L1385*W918*H2005mm	L1685*W1300*H2005mm
Weight	350KG	450KG