

HG Economical Shrink Sleeve Applicator (HLM Series)



INFORMATION

- 1. Stainless steel head cover&machine body ensures superior economy, rigidity and stability.
- 2. Unique designed rotating blade features optimal rigidity and smooth motion. With internal sensor, origining system is totally automatic.
- 3. Mandrel easily positioned, providing efficient changeover.
- 4. Equipped with HMI, providing easy operation.
- 5. Succinct machine structure minimizes the possibility of trouble and optimizes the maintenance.
- 6. Light weight design for great mobility, cantilever type sleeve holder attached with machine body.
- 7. Work with all other auxiliary devices and shrink tunnel, the real machine for your choice.
- 8. Equipped with intelligent memory settlement when sleeving multiple bottle types at different speed, providing user-friendly and convenient changeover.



SPECIFICATION

| | 機 型 Model | HLM-1100 | HLM-1150 | HLM-1200 |
|-----------------|--|--|------------|------------|
| MACHINE 主 機 | 長×寬×高(mm) Dimension(L x W x H) | 980x670x2040 | | |
| | 重 量 weight | 450kg | | |
| | 電 源 Electric Power | AC-3 Phase 220V / 2.5KW | | |
| | 速 度 Speed | 20~100 BPM | 20~150 BPM | 20~200 BPM |
| CONTAINER 容器 | 直 徑 Diameter | φ15-125mm | | |
| | 高 度 Height | Max. 350mm | | |
| | 材 質 Material | 玻璃、金屬、塑膠 Glass, Metal, Plastic | | |
| | 形 狀 Shape | 圓、橢圓、方形、長方形 Round, Oval, Square, Rectangular | | |
| SHRINK | 材 質 Material | PVC, PET, OPS, PLA | | |
| SLEEVE 收縮 | 厚 度 Thickness | 0.035-0.08mm | | |
| 膜材 | 膜料紙管內徑 Inner diameter of sleeve roll | 5"~10" | | |