

D-339F-QP Series Packing Machine



D-339F-QP series packaging machine is for the sauce body, paste and other materials to achieve automatic packaging and design of the three pairs of roller packaging machinery. The machine can achieve three-side sealing of the packaging.

Features:

- The machine has a set of vertical sealing roller means, a set of transverse sealing hot roller means, and a set of transverse sealing cold roller means.
- Seal with roller way, the vertical sealing pattern with checkerboard pattern with leak-proof line, horizontal sealing pattern with checkerboard pattern with anti-leakage line or flat with anti-leakage line.
- The metering device selects a pneumatic piston pump (QP) for no uniform sauce packaging.
- Cut the knife can be used flat knife, jagged, one-way one of the three ways.
- The machine is also equipped with easy to open the bag easy to tear device.
- Variable frequency motor drive, to achieve the packaging speed within the rated range Promise adjustment.
- The series of packaging machines using PLC control touch screen display running status.
- Servo drive transverse sealing mechanism, to achieve bag length can be adjusted within the rated range Promise, bag length on the touch screen for digital settings; bag length adjustment is simple and convenient.
- Intelligent photoelectric color positioning control system, with the first bag automatic positioning function, can automatically exclude due to abnormal color patterns and poorly printed packaging materials caused by the interference signal, stable and reliable operation.

Technical characteristics and uses:

Usually used in food, medicine, pesticides, and cosmetic aspects of homogeneous and heterogeneous viscous, paste and paste materials such as packaging.

Name	Content	Remarks
Bag length range	45-180mm	When the bag length is changed, it needs to be replaced
Bag width range	30-150mm	Change the width of the machine to be changed
Fill capacity	10-300ml	Choose one of the ranges
Packaging speed	20-60Bag / min	Depending on the material and specifications
Power	about 3kw/AC380v	
Mechanical size	L1200mmW1000mmH1800mm	
Mechanical weight	about 550kg	
Adapt to packaging materials	PET/AL/PE、PET/PE、OPP/PP	
Packaging material parameters	Roll membrane diameter ≤ 400 ; roll membrane diameter $\varnothing 75$	
Standard feeding method	Pneumatic piston pump	
Standard cut mode	Flat knife, serrated knife, dotted knife	Three choose one
Optional device	Hot stamping device, printer, level inspection, double bucket, mixing device, product output belt machine	Order separately