



Automatic L-bar Sealing Machine & Shrink Tunnel SGM-400L



Single and group products of medicine, food, drinking, stationery, printings, cosmetic, electronic products, toys, auto parts, tableware, etc.

Technical data:

| | |
|----------------------------------------------|------------------------------------------------|
| Sealing type | L-sealing by means of L-bar |
| Power supply | 380V/50-60Hz/3phase |
| Max Packing capacity | 35 packs per minute(depends on product size) |
| Sealing height | ≤125mm |
| Packing width | ≤350mm |
| Power consumption | 1.5kW |
| Product size | width+height≤400mm length+height≤480mm |
| Film type | center-folded polyolefin(POF)film |
| Max film size | 530mm(width)×280mm(outer diameter) |
| Working height | 780-850mm |
| Air pressure | ≤0.5MPa(5 bar) |
| Sealing system | permanently heated seal bar coated with Teflon |
| Machine material | carbon steel |
| Weight | 300kg |
| Technical data SGM-450C Shrink tunnel | |
| Power supply | 380V/50-60Hz/3phase |
| Oven size | 1200mm(L), entrance 450(W)×220(H)mm |
| Conveyor speed | Variable,40m/min |
| Conveyor | chains with rotating silicon coated rods |
| Power consumption | 7kW |
| Machine material | carbon steel |
| Weight | 160kg |