

ZL300 Automatic Packing Machine



Suitable for fully automatic packing of granules, strips, slices, lumps, powders, and sphericals, etc.

Main characteristics & Structure features:

1. This machine is equipped with double servo driving control system. Servo single paper pulling or servo double paper pulling can be chosen based on product features and different packing materials, and paper pulling system by vacuum adsorption can also be chosen.
2. The end sealing system controlled by servo can carry out automatic setting and adjustment of end sealing pressure and openness of cutters.
3. Diversified packing styles can be performed including pillow type package, side ironing package, gusseting package, and triangular package, punching package, multi-bags conjoint package and multi-bags conjoint package with half bag punched.
4. Some extra devices can be equipped on the machine, such as computerized multi-head weigher, auger filler, electronic scale, volumetric cup filling device and so on, ensuring accurate measurement.
5. The machine design conforms to National GMP standard, and the electric safety protection system has passed CE norm.

Model:	ZL300
Bag size :	L: 80mm-400mm
	W: 80mm-280mm
Packing speed:	15~70bags/min
Power supply:	220V 50Hz 1Ph
Compress air consuming:	6kg/cm ² ,300L/min
Machine noise:	≤75db
General power:	4.2kw
Weight:	900kg
Outer dimension:	2125mmx1395mmx1690mm