

AUTOMATIC VIAL STICKER LABELING MACHINE LSL 200R



Laxmi Pharma Equipment offers Automatic High Speed Sticker Labeling Machine Model: LSL 200R, user friendly, Vertical Linear Sticker Labeling machine suitable for labeling round containers which are previously filled and sealed. No change parts are required for change in container size. As the machine is servo motor operated, a customer has an added advantage to run the machine with a minimum required output to maximum of 200 Labels per minute but depending upon the Label Size and Quality.

The most elegantly designed versatile linear labeling machine to meet the needs of major users of modern packing lines, requiring high efficiency with speed, accuracy and durability. All the adjustments are completely user friendly and requires minimal tools

Silent Feature:

- No change parts are required for change over of container size.
- Synchronized speed of Label Dispensing, Conveyor and Pressing Device
- Self protected against any voltage fluctuations.
- PLC based system with touch screen HMI.
- Suitable for On-Line Ink Jet and Contact Coding System
- Online rejection system (if required)
- Suitable for Partial, Full Wrap Around and Overlap Labeling
- High Production Speed up to 200 containers/min
- Easy to change label application height
- Conveyor & servo speed synchronized and controlled from HMI.
- In built Speed Indicator & Counter
- User Friendly Label Placing Adjustments
- There is no requirement of Oil or Grease for maintenance

Application:

- Pharmaceuticals
- Ayurvedic
- Herbal
- Pesticide
- Cosmetic
- Chemicals
- Food
- And in other allied company and industries

TECHNICAL SPECIFICATION	
Model No	LSL 200R
Label Height	10mm to 90mm
Label Length	12mm Minimum
Gap Between 2 Labels	Minimum 3-5mm
Label Roll Dia	300/ 400mm
Core Dia	75/76mm
Power Characteristics	220v, 1 Phase, 50Hz, 1.2kw
Speed	100-200 labels per minute (Depending on label size & Container)
Conveyor Height	800 – 850mm
Conveyor Lenth	1500 – 1800mm
Net Weight	400 kgs
Machine Length	930mm
Machine width	930 mm with applicator
Machine height	530