

Auto Cap Banding Applicator HLC Series



Product Range

- High Speed Shrink Sleeve Applicator
- Super Speed Shrink Sleeve Applicator
- Standard Shrink Sleeve Applicator
- Auto Cap Banding Applicator
- Economical Shrink Sleeve Applicator
- Steam Shrink Tunnel
- Electric Shrink Tunnel

Features

- Stainless steel made housing with elegant appearance and compact structure.
- Rotating knife plate features optimal rigidity and smooth motion. With internal sensor, origining system is totally automatic.
- Mandrel easily positioned, providing efficient changeover.
- Equipped with HMI, providing easy operation.
- Succinct machine structure minimizes the possibility of trouble, and modular design optimizes the maintenance.
- Light weight design for great mobility, cantilever type sleeve holder attached with machine body.
- Specially designed for cap/neck sleeving: slant sleeving makes sleeving for even small diameter smooth and stable.
- Work with all other auxiliary devices and shrink tunnel, the real machine for your choice.
- Equipped with intelligent memory settlement when sleeving multiple bottle types at different speed, providing user-friendly and convenient changeover.

Specification

	Model	HLC-2150	HLC-2250	HLC-2350
Machine	Dimension (L W H)	980 x 670 x 2040 mm		
	Weight	450 kg		
	Electric Power	AC - 3 Phase 220 V / 2.5 kW		
	Speed	150 BPM	250 BPM	350 BPM
Container	Diameter	Ø 10 - 125 mm		
	Height	Max 350 mm		
	Material	Glass, Metal, Plastic		
	Shape	Round		
Shrink Sleeve	Material	PVC, PET, OPS, PLA		
	Thickness	0.035 - 0.1 mm		
	Inner Diameter of Sleeve Roll	5" ~ 10"		