

HESLY

Automatic Reverse Film Flow Wrapper KD-260A/350A



Suitable for more material blocks such as betel, olives, candies fruit, dates, multiple packet soup, solid dispersing materials, small electronic components of irregular objects.

Features:

Compact structure, stable function and simple operation.

The first third-generation double frequency control the bag could be set and cut, unnecessary adjust air without changing film color code tracking one pace reaches the designated position, it's saving time and film.

It adopts imported electric appliance, touch man-machine interface, convenient parameter setting.

Self-checking function, trouble can be read easily. High sensor photoelectric color chart tracking, make the cutting position more correctly.

Dependant temperature PID controlling suitable for various materials of packaging membrane.

Position stop function, no adhesive and no waste of membrane.

Clean rotation system, more reliable operation and more convenient maintenance.

All the controlling operates by the software, convenience for function adjustment and technical upgrading.

Main Technical Data:

Model	KD-260A	KD-350A
Max.film width	260mm	350mm
Max packaging capacity(according to its material to fix)	50-220p/min	50-220p/min
Suitable film thickness	0.03-0.06mm	0.03-0.06mm
Length of bags	60-200mm	60-200mm
Packaging with	25-100mm	50-150mm
Packaging height	5-45mm	5-45mm
Intensity of Sealing	≥15	≥15
Total power	2.4Kw 220V 50hz	2.7Kw 220V 50hz
Overall dimensions(L x W x H)	4100x920x1500	4000x1000x1500
Weight	550kg	600kg