

Side Sealing Shrink Wrapping Machine SUK-4550 / SUK-RS-5030



Main performance and structure features:

1. Fully automatic shrinking machine, which is widely used in the batch production of running water, high efficiency, automatic film and punching device and manual adjustment of the guiding membrane system and manual adjustment of feeding platform, suitable for different width and height, the model also has the function of secret sealing, specially designed for small package products.

The seal knife uses the United States deteriorate coating anti - sticky high - temperature aluminum alloy knife, the seal will not crack, will not coking, no smoke zero pollution.

2. Equipped with imported detection photoelectric, horizontal and vertical detection of each group, easy to switch, for thin and small packaging, can easily complete closure packaging operations.
3. Automatic feeding, length can also be automatically adjusted by the combination of electric eye and timer. Equipped with induction motor, automatic coiling scrap.
4. When the size of the packaging change, the adjustment is very simple, no change of mold and bag - maker.
5. Different sizes of products can also be combined with packaging to achieve the promotional effect.
6. The thermostat uses the original " Omron" digital temperature controller, built-in PID function, the knife temperature is extremely sensitive and accurate, can be set at will. Do not have to worry about the temperature does not accurately and damage products, the knife itself also with automatic protection function, effectively prevent the by mistake packaging.
7. The machine seal part is equipped with an organic glass protection cover, with automatic alarm function, greatly improving the operator's safety.

8. The whole set of machine is really connected with the unmanned operation of the production line.

Application:

This Sealing Shrink Wrapping Machine Applicable to food, cosmetics, printing, pharmaceutical and floor, ceramics, beverage, hardware and other industries in large volume shrinkage packaging Can be equipped with unmanned packaging line, automatic water packaging line and other packaging production line.

Specification:

| Model | SUK-4550 | SUK-RS-5030 |
|---------------------------------|-----------------|--------------------|
| Mechanical size L×W×H (mm) | 1700×960×1400 | 1640×780×1625 |
| Maximum packing size L+H (mm) | ≤500 | 1000×450×250 |
| Maximum packing size W+H (mm) | ≤430 (H≤100) | |
| Maximum seal size L×W×H (mm) | 550×450 | |
| Packing speed (part / minute) | 10-30 | 20~50 |
| Net weight (kg) | 225 | 250 |
| Power (kw) | 1.3 | 13 |
| Power supply | 220V50/60Hz | 380V 50/60Hz |
| Use gas source (kg/cm3) | 5.5 | 5.5 |
| Maximum current | 10 A | 30A |
| Feeding level height (mm) | 820±30 | 820±30 |