

SFS-100 Plastic Tube Filling and Sealing Machine



Key Features:

- Ø Compact Design
- Ø Driving Parts Fully-closed
- Ø Pneumatic Tube Washing & Feeding
- Ø Intelligent Temperature Control and Cooling System
- Ø Easy to Operate and Adjust
- Ø 316L Stainless Steel Contact Parts to meet GMP Standard
- Ø Safety Interlock Shutdown when Door is Open
- Ø Overload Protection Provided
- Ø Automated Working process from Tube Loading to Finished Products Output
- Ø Automatic Orientation Effected by Photoelectric Induction

Optional Devices:

- Ø Chiller
- Ø Date Coding Embossing
- Ø Automatic Tube Feeding Magazine
- Ø Change Parts

Technical Parameters:

Filling volume	1-400ml/unit (Adjustable)
Filling accuracy	$\leq \pm 1\%$
Capacity	1800-4800unit/hour, Adjustable
Tube diameter	$\Phi 12-60$ mm
Tube length	50-240 mm
Hopper volume	40L
Power	380V/220V (Optional)
Air pressure	0.4-0.6 MPa
Equipped motor	1.1KW
Machine power	5kw
Inner wind motor	0.37kw
Convulsions motor	0.37kw
Dimension	2270×960×2100 (mm)
Weight	About 1350 Kg