

Shrink Tunnel-Multipack-4520PD



This is simple and reliable best shrink tunnel with excellent line, hard-working machine that produces superior packages every time. This shrink tunnel can also combine with an L-Sealer for the better wrapping and packaging solution. Standard finish or stainless steel are available two types of machines.

Features

- Full re-circulating air chamber.
- Dual heat insulation plate unable causes around temperature over-hot. The safety shields-protect from heat.
- PID temperature control.
- Conveyor speed for Shrink Packaging Machine adjustable. Adjustable air velocity control.
- Conveyor chain used the solid roller, exterior is packed by high temperature silica gel, burden with heavy products.
- Roller rod conveyor. Teflon mesh overlay is optional.
- The electrical control parts have overheated compensator protection to shut off the power.

Specification

MODEL	CN-4520PD	CN-6530PD
Power Supply	3φ,220V/380V	3φ,220V/380V
Power consumption	9 KW	15 KW
Tunnel size	L=1000 x W=450 x H=200mm	L=1000 x W=650 x H=300mm
Conveyor speed	10M/min	10M/min
Conveyor size	L=1400xW=450xH=760mm	L=1600xW=650xH=760mm
Machine size	L=1400 x W=760 x H=1450mm	L=1600 x W=960 x H=1550mm