



FL-5545T+SM-4525 Manual L Bar Sealing and Shrink Tunnel System



Suitable for the packing demands of the mass production in industries such like electronics, hardware, plastic, software, food, printing, pharmaceuticals, floors and other construction materials.

Applicable films: PVC/POF.

Shrink Tunnel Technical Features:

- Stainless heating tubes and strong blowing motor ensure high heating efficiency, large air volume and uniform air circulation.
- Solid metal rods wrapped by heat-resistance silicone tubes make the Conveyor rollers strong and resilient.

Manual L Bar Sealer Technical Features:

- Teflon coated sealing wires in glass-fiber slots, making the seam straight, closed and unburnt.
- Miscasting and overheating protection devices can effectively protect the products and the operator.
- Tailored perforators to fully evacuate the air from the film bags.
- FL-5545TB/7555TB cut and seal by cylinder, saving physical strength while improving the efficiency.

Dimensions:

Model	FL-5545T	SM-4525
Machine Dimensions (mm)	1570 X 750 X 1020	1300 X 746 X 1465
Max Packing Size (mm) L+H(mm) H<200	≤500	700 X 350 X 200
Max Packing Size (mm) W+H(mm) H<200	≤400	
Max Sealing Size (mm)	550 X 450	/
Capacity (pcs/h)	800~1000	0~15 m/min
N.W. (kg)	125	260
Power (kw)	1.2	9
Power Source	PH 220V 50/60Hz	3PH 220V/380V 50/60Hz
Air Source (kg/cm ²)	/	/
Applicable Film	POF/PVC	POF/PVC