

## *Packing conveyor belt*



The conveyor belt brings the container or products from the labeling/blister/strip machine.

The packing conveyor belt is having stainless steel table top with moving endless sandwich belt in the center. Tabletop is fixed to the same structure made out of SS square pipe & supported on adjustable bolts. Tabletop is of 12 inches working space on both side of the conveyor belt for final visual inspection & packing into the box.

### **Specification**

#### **SALIENT FEATURES**

1. Structure is made of S.S. 304, 30 mm sq. pipe, 16 SWG with matt finish.
  2. A/c frequency variable drive.
  3. Belt-alignment system for long life & straight running of belt. Direct gear drive.
  4. Length can be made as per customer requirement.
  5. S.S. elegantly matt finishing.
  6. Adjustable height of conveyor belt, to align with other machine of the line
  7. Self-alignment bearing for easy maintenance.
  8. Rigid vibration free construction for trouble free performance.
- Direction of Movement Left to Right Speed\*\* 7.5 Mtr./Min. upto 12 Feet Long 12 Mtr./Min. from 13 Feet to 24 Feet Long
  - Power Characteristics\*\* 0.25 HP/220 V/50 Hz up to 12 feet long 0.5 HP/220 V/50 Hz from 13 feet to 24 feet long.
  - Height of Conveyor\*\* 860 mm to 910 mm
  - Belt width\*\* 9" or 12" as per requirement.

- Belt Details\*\* PVC, endless 2 ply sandwich, 2mm thickness.
- Machine Dimensions\*\*
- 9" width belt As per requirements (L) x 830 mm (W) x 910 mm (H)
- 12" width belt As per requirements (L) x 900 mm (W) x 910 mm (H)
- Case Dimensions\*\*
- 9" width belt As per requirements (L) x 1050 mm (W) x 1150 mm (H)
- 12" width belt As per requirements (L) x 1100 mm (W) x 1150 mm (H)
- Net Weight Depend on Length
- Gross Weight Depend on Length