



## ***KS-160B Automatic Double Aluminum Strip Packaging Machine***



Automatic Double Aluminum Strip Packaging Machine KS-160B, is characterized of advanced structure, high efficiency, low noise and easy to operate. Utilizing frequency control to set travel at will, and increases the vibration entire column feed mechanism and optical monitoring devices, it can automatic counting, and can Auto-complete filling, sealing, tangent, batch number, cut at high-speed operation. For package made on KS-160B has good sealing and well lucifuge to greatly extend the shelf life of the product, and bring carry convenience, KS-160B packaging machine is applicable to package all kinds of tablets, capsules in the pharmaceutical industry, and electronic components in electric industry.

### **Features:**

1. The machine shell is made of welded stainless steel plate by forming, the KS-160B is designed into safe operation with protective PC board door cover, which meets GMP demands and greatly enhance aesthetics and practicality of products.
2. Ten tire device uses programmable controller and programmable touching screen to control each action point, so it can be ensure that uncoated or coated tablets and capsules can be automatic filling into two level of Alu materials became to strip packing. Besides, the length of strip sheet (the strip traction) can be change by the touching screen as your required, you just adjusts some rollers and remove some cutter easily when you want to change the strip packing length or different sheet.
3. The TEMP of heating sealing mould is control by intelligent temperature controller with PID system, meanwhile, the TEMP detector is adopts PT roller surface detector which components is imported, one the one hand, it can be ensure the stable TEMP of roller surface, on the other hand, it can increase leak-proofness of heating strips.

4. The speed of main motor is control by transducer which is steeples speed regulating, it adopts programmable controller, so it can be make the drive of mechanical frame simple, easy to maintain. Suitable for packaging machine small business.

5. In addition, the machine also have cutter in sealing station, which is for waster edge easy to tear, it can be make the trips look more clearly and nice looking.

Technology parameters:

<b>Model</b>	<b>KS-160B</b>
Capacity (pieces/minute)	800
Blanking Frequency(time/minute)	40~80
Air Compression(Mpa)	0.5
Max length of pacakging material (mm)	160
diameter of coiled material(mm)	300
Power(kw)	2.75
Weight (kg)	450
Dimension(mm)	1300x750x1700