



HXLB-K100 Automatic Rounded Strip Automatic Packaging Machine



Performance characteristics:

1. The machine adopts advanced full computer touch screen operation, man-machine interface, and the operation is simple and convenient. The internationally renowned brand PLC control system can automatically complete bag making, metering, filling, filling, sealing, slitting, counting, coding, punching and rounding.
2. Intelligent photoelectric control device ensures the integrity of the packaging bag making pattern.
3. Independent research and development adopts servo + CCM silent linear sliding table pulling bag technology to make the packaging more flat and the bag length is accurate.
4. The overall contact material parts and casing are made of 304 stainless steel, which meets the food and drug hygiene permit standards.
5. This machine is suitable for sealing in the form of back seal. The cutting method uses imported die technology, and can be customized to cut the incision.
6. Advanced design to ensure that the machine is suitable for different industries in the use of adjustment, operation, maintenance are very convenient. It can be used together with various automatic metering equipment at home and abroad.
7. Can be packaged multi-layer composite film, polyester / polyethylene, polyester / aluminum foil / polyethylene polyester / aluminized / polyethylene, paper / polyethylene, a wide range of packaging.

Scope of application:

Granule type: Granular materials with good fluidity such as plastic granules, fertilizer granules, feed granules, chemical granules, chicken essence, monosodium glutamate, white sugar, seeds, coffee, whole grains and so on.

Powder machine type: flour, seasoning powder, additives, chemical powder, medicinal materials and other powders.

Semi-fluid models: fluids and semi-fluid materials such as honey, jam, vegetable oil, soy sauce vinegar, lotion, liquid medicine, etc.

Technical parameters:

型号	HXLB (K/F/S)100
制成袋长	40-190mm
包装薄膜宽度	6-200mm
包装膜厚度	6-12um
包装容量	5-100ml
包装速度	25-50bags/min
功率Kw	3KW
电压	220v50HZ (60HZ)
外形尺寸mm	800(宽) ×1200 (长) ×1800 (高)
整机重量	350Kg