



EN600SPS Mini Wrapper



EN600SPS min stretch wrapper is used for wrapping single cargo or some small cargoes combined. Pneumatic top plate ensures it clam and safety packing.

Features:

- Advanced control system
- PLC Control
- Easy to set parameters via panel as following:
Top /Bottom wrap times, Carriage up/down times
- Powered pre-stretch film carriage up to 200%
- Cycle pause capacity
- Film tension, turntable speed separate adjustment from the control panel
- Separate Auto-Start/Reset, Pause & E/S buttons
- Minimum maintenance
- Pneumatic top plate ensure packing clam and safety
- Film delivery variable speed by separate AC Drive Motor & Separate inverter

Specification:

Size of the product to be wrapped

Min load size (LxWxH)	300 x 300 x 300 mm
Max load size (LxWxH)	600 x 600 x 450 mm (Tailor-made according your size)
Max weight	100KG

Film Carriage

Carriage	Power pre-stretch film carriage, stretch ratio up to 200%
	Film tension adjustable

Machine Specification

Turntable speed:	20 rpm
Turntable size	400 x 400 mm (LxW)
Turntable height	690 mm
Carriage	Fixed

Power supply voltage	220 Volt 1 Ph - 50 Hz
Power	0.8 Kw
Packing efficiency	20-40 loads/hour
Air consumption	20 L/min
Machine size	1150 x 600 mm (LxW)
Machine weight	220kg

Stretch Film Roll detail

Max. external diameter (D):	230 mm
Internal diameter (d):	76 mm
Film roll height (h):	500 mm
Film thickness:	17-35 μ m