

Vertical Packaging Machine SN-420/520/720/820



It's suitable to use in packing the high accuracy and easy fragile material, such as: puffy food, crispy rice, jelly, candy, pistachio, apple snices, dumpling, and chocolate, pet food, small hardware, medicine, etc.

Feature:

1. PLC control with stable, reliable biaxial high accuracy output and color touch screen, bag-making, measuring, filling, printing, cutting, finished in one operation.
2. Separate circuit boxes for pneumatic control and power control. Noise is low, and the circuit is more stable.
3. Film-pulling with vacuum double belt: less pulling resistance, bag is formed in good shape with better appearance, belt is resistant to be worn-out.
4. Double servo control, high precision orientation, size more nicety.
5. External film releasing mechanism: simpler and easier installation of packing film.
6. Adjustment of bag deviation just needed to be control the touch screen. Operation is very simple.
7. Close down type mechanism, defending powder into inside of machine.

Technical Parameters:

Model	SN-420	SN-520	SN-720	SN-820
Bag length	80-320mm(L)	80-420mm(L)	100-500mm(L)	100-550mm(L)
Bag width	50-200mm(W)	50-250mm(W)	100-350mm(W)	180-400mm(W)
Max width of roll film	420mm	520mm	720mm	820mm
packing material	OPP/PP,OPP/PE,PET/PE			
Packing speed	5-60bags/min	5-50bags/min	5-40bags/min	5-30bags/min
Measuring range	150-1500ml	150-2000ml	500-3500ml	6000ml(Max)
Power voltage	220V 50/60hz 2.2kw	220V 50/60hz 2.5kw	220V 50/60hz 3kw	220V 50/60hz 5kw
Machine weight	500kg	550kg	600kg	900kg
Machine dimension	(L)1388×(W)1116 ×(H)1536mm	(L)1440×(W)1216 ×(H)1796mm	(L)1500×(W)1116 ×(H)1536mm	(L)1780×(W)1350 ×(H)1950mm