



Link-50P Automatic Flaps Folding Carton Sealing Machine



Link-50P left and right drive + up and down drive carton sealing machine with top belt drive on both sides of the lower side, using sticky tape sealing, upper and lower sealing, fast and stable, and the sealing effect is smooth, standardized and beautiful, and can be adjusted manually according to carton specifications Width and height, simple, fast, convenient and can replace labor, improve production efficiency by up to 80%, save 5-10% of consumables, is a good choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization. The drive carton sealer is also called the up and down drive carton sealer, which is manually adjusted according to the size of the carton.

Features of carton sealing machine:

·Manufactured with international advanced technology, and selected imported parts and electrical components;

The standard machine table height is 600mm;

· Manually adjust the width and height according to the carton specifications;

·Using the lower side and the top belt drive, suitable for wider and heavy cartons;

·Equipped with blade guard. Avoid accidental stabbing during operation;

Manually fold the upper cover, and seal the box with the upper and lower characters at one time;

·It can be operated on a stand-alone machine, or it can be used in conjunction with an automated packaging line. It is the choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization.

Application range of sealing machine:

Relying on the above advantages, the upper and lower drive case sealing machines are widely used in food, medicine, beverages, tobacco, daily chemicals, hardware, toys, electronics and other industries at home and abroad.

Technical Parameters:

Model	Link-50P
Applicable to the power supply	220V/50Hz / 0.4KW
Work pressure	5-6 kg /cm ² 150 n/ min
Minimum packing size	L 150 * W 180 * H 150mm
Maximum packing size	L Unlimited * W 500 * H 500mm
Mesa height	H 600mm-650mm
The belt speed	20 m / min (4-6 kes / min)
Packing tape	BOPP/PVC
Tape size	W48, 60, 75mm
Installation dimensions	L 1000 * W 900 * 1370mm
The net weight	155Kg