

Mini Shrink Tunnel-Multipack-4520A



Heating circulating type shrink tunnel is most cost effective and suitable for PVC film. CN-4520A shrink tunnel can be combined with L-Sealer for best wrapping solution. It is available in standard as well stainless steel. CN-4520AL is framed in POF films.

Features

- Heat Shrink Packaging Machine using infrared ray heater, PVC films or POF films are available for our machines.
- The conveyer speed for heat shrink is controlled by precision electric stepless type instrument, speed is adjustable and highly stable.
- Heat Shrink Packaging Machine is light and small. Its legs can be dismantled easily in order to save space
- Heat Shrink Packaging Machine saves electricity and shrinks fast.
- Adopting automatic temperature controller or constant temperature controller (according to customer need).
- The conveyer belt for Heat Shrink Packaging Machine can be made in to roll type, net type or Teflon net according to the character of the products.

Specification

MODEL	CN-4015A	CN-4520A	CN-4520AL
Power Supply	1φ, 220V/240V	1φ, 220V/240V	3φ, 220V/240V
Power consumption	5 KW	6 KW	9.6 KW
Tunnel size	L=700xW=400xH=150mm	L=800xW=450xH=200mm	L=1000xW=450xH=200mm
Conveyor speed	0~10M/min	0~10M/min	0~10M/min
Conveyor size	L1050xW400xH690mm	L1200xW450xH690mm	L1500xW450xH760mm
Machine size	L=1180xW=620xH=1050mm	L=1330xW=720xH=1100mm	L=1650xW=720xH=1220mm