

Film Bottom Feeding Packing Machine DXD-280



DXD-280 Film Bottom Feeding Packing Machine is suitable for pillow type packing products without stable shapes.

Technical Specification

1. This flow packing machine has different product feeding system for needs of products.
2. There are servo motors control version and double frequency version for customers' choice.
3. Width of film roller is 300mm, which means, max. Film width could be used on this horizontal packing machine is 300mm.
4. 1.9-2.7meters feeding conveyor allows enough space for manually feeding.

Technical Parameters

Max.Production Capacity	最大生产能力	50-190包/分 (bags/min)	50-190包/分 (bags/min)	50-190包/分 (bags/min)
Packing shape	包装物形	各类形状Various shapes	各类形状Various shapes	各类形状Various shapes
Packing Range	Length of bag	袋长	150-450mm (单刀Single Cutter)	70-260mm (双刀Double Cutters)
	Width	宽度	25-110mm	25-100mm
	Height	高度	≤50mm	≤50mm
Max.Dia.of Film	包装膜最大直径	300mm	300mm	300mm
Max.Width of Film	包装膜最大宽度	350mm	350mm	350mm
Gross Power	总功率	3kw	3kw	3kw
Power Supply	电源	220V 50-60Hz	220V 50-60Hz	220V 50-60Hz
Gross Weight	总重量	750kg	750kg	750kg
Overall Dimension	外形尺寸	3200-4700×1050×1450mm	3200-4700×1050×1450mm	3200-4700×1050×1450mm
Packing Material	包装材料	OPP、CPP、PET镀铝膜、铝塑膜、纸塑、纸胶等单层多层等可热封材料 建议使用外层PET厚度0.013mm,内层CPP厚度0.023~0.027mm,复合低温膜 OPP、CPP、PET Metallized film, Al-plastic film, Paper-rubber complex Suggest to used wrapping film with material of PET13/CPP23-27		

Note: We can design and manufacture according to customer's special needs. 注: 用户如有特殊规格, 本公司可另行设计制造。