

Continuous Sealer Machine FRM-1010I



FRM-1010I is a heavier duty model compared to our FRB and FR band sealer lines and offers the best sealing quality on the market.

- Durable stainless steel.
- Solid state temperature controller to maintain seal bars at proper temperature for consistent seal quality.
- Fully adjustable conveyor (the conveyor height and depth in relation to seal bars can be adjusted).
- Motorized rubber conveyor for speed control.
- Knurled pressure rolls with variable pressure adjustment.
- One pair each of cooling and heating blocks.
- Sealing method - constant/direct heat accompanied with a pair each of cooling and heating blocks.
- Dry ink coding allows for printing on the seal line - 18PT.
- Unit feeds right to left.
- Equipped with an emergency stop button.

Parameters:

Model	FRM-1010I
Voltage (V/Hz)	AC 220/50 110/60
Motor Power (W)	100
Suction Pump Power (W)	-
Sealing Power (W)	400×2
Printing Heating Power (W)	40×2
Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10

Temperature Range (°C)	0-300
Printing Type	Solid-Ink Roller
Distance from Sealing Center to Conveyor Table (mm)	10-40
Distance from Base plate to Interior Conveyor (mm)	85-115
Conveyor Table Size (L × W) (mm)	1065×205
Overall Conveyor Loading (kg)	≤3
External Dimensions (L × W × H) (mm)	1065×460×360
Net Weight (kg)	41