

WP-HD series Two Bag Formers VFFS Packing Machine



Application

- ◎ Applicable Bag Type: pillow bag.
- ◎ Applicable Film Materials: a variety of laminated films, single-layer PE film; film thickness range 0.03~0.15mm
- ◎ Applicable Products: snack food, chemical raw material, pharmaceutical, small hardware, such as candy, bean, pet food, dried fruit, sugar, seasoning, small granule stuff, etc.

Feature

- ◎ Both film pulling driven system and horizontal sealing driven system controlled by servo motor. Bag length can be controlled by optical tracking and specification adjustment. (extra encoder is available) Mechanical coding adjustment device.
- ◎ Panasonic PLC control, rotatable man-machine interface screen, user-friendly operation and UI option. Two lines processing controlled by the same PLC system.
- ◎ Machine is compatible for different fillers or weighers. Simplify operation with lower maintenance cost.
- ◎ Double filling device, more stronger capacity of packing process.
- ◎ Film pulling system equipped with three phases speed control, which makes machine run smoothly.
- ◎ Equipped with danger detecting device, auto-stop protection when door opening, horizontal seal clamp alarm, no film alarm, no ribbon alarm and so on.
- ◎ The frame is made of #304 stainless steel.

Technical Parameters

Model	WP-HD3830
Film Width	140-380mm
Bag Size Range	L*W=(40-300)*(60-180)mm
Packing Speed	90*2=180 (bags/min)
Voltage	6.5KW/220V/50(60)Hz
Gas Pressure	0.4~0.8MPa
Gas Consumption	0.4m ³ /min
Machine Size(mm)	2270*1560*1880
Machine Weight	900KG