

SA-106-2 Automatic Sleeve Wrapper - For Bottles



Machine features

- Suitable for round shape products, such as: can, tin, bottle...etc., non-tray product.
- Machine combine seal & shrink functions for completed package.
- Infeed belt with product swing & alignment function.
- Package process: product alignment → film wrapping → sealing & cutting → outfeed conveyor → shrink tunnel → package completed.
- Suitable for PE film package.
- Enable to change product alignment mode according to product.
- Fixed device on the top of product, ensure no movement while sealing & cutting.
- Adjustable product delivery speed, pushing timing, positioning sealing timing...etc.
- Attach air flush to cool sealing in a short time for good strength.
- Equip product entry sensor for smooth filling process.
- Mitsubishi PLC controller.
- Temp. controller with PID function and driven by SSR for stable heating performance.
- Cutting blade made by one piece for long time operation stability.
- Auto delivery product into shrink tunnel after wrapping.
- Shrink temp. & speed are adjustable.
- Cooling fan in the rare of tunnel.
- Inner tunnel related heating parts are mainly made by stainless steel.
 - 5-6kg/cm² filter is provided by buyer.

Applicable products

Beer, alcohol drinks, soda, water, can, bottle, glass, milk, healthy drinks, PET bottle, non-tray group package...etc.

Specifications

Model	SA-106-1(Single Line)	SA-106-2(Double Line)
Machine	L 5170 x W1450 x H 2050mm	L 5170 x W 2350 x H 2050mm
Package Range	L 360 x W240 x H180mm	Customized
Speed	1-22 pack /min	1-44 pack/min
Power	220V/380V/415V(upon request)	
Power consumption	25KW	50KW
Air consumption	380L/min	760L/min
*Package speed will be differ from product size, shape, film and operator.		