



## *CGFR series Flushing Hot Filling Screw Cap Three in One Machine*



CGFR series fully automatic rinsing, filling and rotary capping combined machine, whose main technique was imported from Italy, can realize to asepsis filling. Because it is equipped with constant temperature controlling system. It can apply to fill hot fruit juice, tea and other beverage into thermal proof PET bottle by changing few parts. The complete set of machine is more advanced in technique, compact structure, it is suitable for normal temperature filling or hot filling PET bottled no gas contained beverage (Mineral water, purified water, distilled water, fruit juice, tea and so on).as well as washing, filling and sealing other liquid, such as vinegar. It is one of the most advanced filling machines at present.

**主要技术参数 Main Technical parameters**

| 型号             | Model                              | CGFR16126                             | CGFR18186      | CGFR24248      | CGFR32328      | CGFR404012     | CGFR505012     | CGFR606015     | CGFR808020     |
|----------------|------------------------------------|---------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 冲洗、灌装、旋盖头数     | Heads of washing, filling, sealing | 16-12-6                               | 18-18-6        | 24-24-8        | 32-32-8        | 40-40-12       | 50-50-12       | 60-60-15       | 80-80-20       |
| 生产能力瓶/时(500ml) | Production capacity(bottle/hour)   | 3000-4000                             | 5000-7000      | 8000-12000     | 12000-15000    | 16000-18000    | 20000-24000    | 24000-28000    | 36000-40000    |
| 适用瓶型规格(mm)     | Suitable bottle                    | H=170-320 $\phi$ =50-100 (330~1500ml) |                |                |                |                |                |                |                |
| 喷冲压力(MPa)      | Spraying pressure                  | 0.25-0.3                              |                |                |                |                |                |                |                |
| 总功率(kw)        | Total Power                        | 2.2+0.37                              | 2.2+0.37       | 3+0.45         | 5.5            | 7.5            | 11             | 15             | 19             |
| 外形尺寸(mm)       | Overall dimension (L×W×H)          | 2100×1750×2500                        | 2500×1860×2550 | 3100×2100×2550 | 3800×3000×2550 | 4650×3300×2550 | 4850×3650×2550 | 6500×5400×2550 | 7650×6400×2550 |
| 重量(kg)         | Weight                             | 2600                                  | 3500           | 4650           | 6800           | 8500           | 10000          | 12500          | 16000          |