

ZL230 Automatic Packing Machine



Suitable for fully automatic packing of granules strips, slices, lumps, powders, and spherical, etc.

Main characteristics & Structure features:

1. This machine is equipped with monoaxial or biaxial servo driving control system. Servo single paper pulling and servo double paper pulling can be chosen based on product features and different packing materials, and the paper pulling system by vacuum adsorption can be chosen to fully keep paper pulling smooth and bag length accurate.
2. To meet user's various demands, two options are available for end seal mechanism: pneumatic driving system and servo driving system.
3. Diversified packing styles can be performed including pillow type package, side ironing package, gusseting package, and triangular package, punching package, multi-bags conjoint package and multi-bags conjoint package with half bag punched.
4. Some extra devices can be equipped on the machine, such as computerized multi-head weigher, auger filler, electronic scale, volumetric cup filling device and so on.
5. The machine design conforms to National GMP standard, and the electric safety protection system has passed CE norm.

Model:	ZL230
Bag size:	L: 80mm-300mm W: 80mm-200mm
Packing speed:	15~70bags/min
Power supply:	220V 50Hz 1Ph
Compress air consuming:	6kg/cm ² ,250L/min
Machine noise:	≤75db
General power:	3.0kw
Weight:	580kg
Outer dimension:	1770mmx1105mmx1500mm