



**HORIZONTAL FLOW WRAPPER**  
**Model# Flow Wrap – 4S**



**Flow Wrap – 4S**

- **Laminated Film - 3 – 5 mil thickness range**
- Advanced PLC Control System with User Friendly Color Touchscreen,
  - Easily Set and Change Packing Parameters
  - Display Production Data and Self-Diagnostics
- Servo Motor Drive System, Film Speed Automatically Synchronized with Conveyor Speed
- End Seal Jaw Speed Easily Adjustable by a Hand Wheel When Changing Bag Length
- Designed for Easy Maintenance and Cleaning
- Pulling Wheels Open by Means of Pneumatic Switches.
- The Sealing Wheels Open Automatically at Every Machine Stop
- Safety Guards Comply with CE Standard

Available Options: Photo-eye for print registration  
 Date Code Printer  
 Line Shaft for Automatic Feeders

<b>MODEL # 4S</b>	<b>4S</b>
<b>Speed</b>	<b>Up to 100 pcs. per minute</b>
<b>Laminated Film Reel Width - Max.</b>	<b>15.75"</b>
<b>External Laminated Film Reel Diameter</b>	<b>13.8"</b>
<b>Max. Package Height</b>	<b>2.75"</b>
<b>Max. Package Width</b>	<b>7.87"</b>
<b>Min. Package Length</b>	<b>2.36"</b>
<b>Max. Package Length</b>	<b>17.8"</b>
<b>Compressed Air</b>	<b>87 psi</b>
<b>Supply Voltage</b>	<b>220 – 240 vac / 1 phase</b>
<b>Power Consumption</b>	<b>2.5kw</b>