

# GOLDEN LIN

## Vertical Form Filler Sealer for Powder GL-1260



Suitable for filling food, medicine, herbs, chemicals and pesticides with 35-65 degrees of repose or allowable breakage of particles, and other non-free flowing powders

1. The filling stop motion is controlled by a magnetic clutch brake system
2. Digital counter provides easy setting of metering range.
3. Comprehensive auger sizes to meet requirements for weighing and filling various powders.
4. Extra wide pulley permits easy setting for filling speed.
5. High precision digital setting temperature control assures accurate setting and a consistent and excellent sealing effect.
6. The sealing blade roller is equipped with a self-lubricating bearing which features high temperature resistance and lubrication free.
7. Parts that powder flows through are manufactured from SUS#304.
8. All SUS304 material surfaces are electrolyte treated for long term smoothness, easy cleaning and meet GMP requirements

### Specifications:

Model	GL-1260S	GL-1260B
Type	3-side sealed	Pillow sealed
Filling Range	5-100g	5-100g
Packing Speed	20-40 bags/ minutes	20-40 bags/ minutes
Bag Length	50-210mm	50-210mm
Bag Width	40-130mm	40-130mm
Packing Speed	20-40bags/minutes	20-40bags/minutes
Accuracy	+/-1%	+/-1%
Power Source	220/380 V, 50/60Hz, 3 phase	220/380 V, 50/60Hz, 3 phase
Power Consumption	3.5 HP/2.6KW	3.5 HP/2.6KW
Machine Size	W700*D1300*H2300mm	W700*D1300*H2300mm
Machine weight	420 kgs	420 kgs