

HYXG-10R-A Automatic Star Wheel Single Head Ropp Aluminium Lid Capping Machine



Automatic Star Wheel Single Head Ropp Aluminium Lid Capping Machine is suitable for aluminum caps. The machine compared with other similar products is notable with the advantages: First, using a four-claw head balance-type for sealing the caps in uniform force; the second is having to make the shape of the bottle by bottle deformation, and then rolling thread flange sealing function. Also, the machine has a beautiful appearance, compact structure, reasonable design, stable operation, low noise, sealing speed, good sealing quality, and suitable for all kinds of wineries, beverage plants, breweries, pharmaceutical plants and other production companies. While the machine is multifunctional by changing different head parts to seal different kinds of caps like three anti-plastic cover cap and cover, chrysanthemum cover.

Working principle of machine: Drive the rotation of main shaft from the dynamic of motor by the gear reducer; The rotation among curve camshafts is converted into the force which drives the capping head to move upward and downward; At the same time the gear reduce drives the curve camshaft in the bottom to make the star wheel move intermittently which matches up with the upand-down movement of capping head. The upper variable speed motor let the capping head works by driving the belt; When the star wheel rotates the bottles below the capping head which punches the binding face between cap inner liner and bottle mouth; Meanwhile the fit thread screw is completed from the flanging and rolling pilfer proof ring. Finally the perfect capping effect comes out. This machine has compact and reasonable structure, it is easy to combine other devices into its production line.

Automatic Star Wheel Single Head Ropp Aluminium Lid Capping Machine is mainly used for bottling of daily chemical, agricultural chemical and pharmaceutics industry.

Main Technical Data

Bottle diameter: Ø20mm~Ø90mm
Bottle height: 80mm~250mm
Cap spec: Ø15mm~Ø50mm
Capping speed: ≤2000 瓶/小时

• Power supply: AC220V/110V, 50/60Hz can be customized

Total power: 2KwWeight: 400Kg

• Demension: 2000×1500×1500mm