

Double Sided Rotary Tableting Machine

27D, 35B, & 45BB Station



It is a square model/double sided rotary tablet Press/ promising unmatched quality for medium batch Production. Safety/enhanced performance/clean ability And ease of operation is its most significant features.

FEATURES

- Robust with high quality Engineering
- Medium batch production
- Safe/ simple to operate and easy to maintain
- Designed as per cGMP standards

Technical parameters

TECHNICAL SPECIFICATIONS			
Model	CM-D-27	CM-B-35	CM-BB-45
Type of Tooling	D	В	ВВ
No. of Stations	27	35	45
Output Tablets/Hr.*	50000 to 129000	70000 to 168000	90000 to 216000
Max. Operating Pressure	10 Tons	6.5 Tons	6.5 Tons
Max. Tablet Diameter	23 mm	16 mm	11.11 mm
Max. Depth of Fill	20 mm	17.5 mm	17.5 mm
Upper Punch Penetration	1.5 to 8 mm	1.5 to 8 mm	1.5 to 8 mm
Main Electric Motor	3.70 kW / 5Hp / 1440 RPM / 415 V / 50 Hz / 3 Ph		

^{*} Depending upon the characteristics of material, shape & size of tablets

NOTE:

DUE TO CONTINIOUS IMPROVEMENTS IN THE MACHINERIES, SPECIFICATION OF THE MACHINERIES IS SUBJECT TO CHANGE WITHOUT ANY PRIOR NOTICE.

