



SK-420 Vertical Packaging Machine



Features:

1. Two synchronous belts device and servomotor film transporting system, makes the film move stably and form bag smoothly.
2. Two independent sealing cylinders, the final bag is excellent airtight and nice sealing stripes.
3. Adopt imported PLC and color touch screen, human-machine interface, high automation, easy to learn and operate.
4. External film feeding mechanism. Film setting is easier and faster.
5. Various automatic alarm protection functions, the maximum reduce wastage.
6. Different bag shapes are workable depend on customers' request.

Applications:

Suitable for packing different kinds of products with different metering devices.

1. Electronic Weighing System
2. Volumetric Cup Metering Device
3. Semi-automatic Feeding Device
4. Auger Filler
5. Liquid Filling and Weighing Device

Optional Function:

1. Air flushing system

2. Nitrogen gas flushing
3. Hole punch device
4. Gusset device
5. Tear notch device
6. Linking bag device
7. Flip device
8. PE bag device

Specification:

Model	SK-420
Air Consumption	0.65Mpa, 3M ³ /min, 6kg/cm ²
Packing Film Width	180-420 mm
Bag Length	80-300 mm
Bag Width	80-200 mm
Packing Film Roll Diameter	Max.360 mm
Packing Speed	5-70bags/min
Packing Film Thickness	0.04-0.08 mm
Power Supply	220V,50/60Hz,2.4Kw
Machine Size	(L)1000x(W)930x(H)1670mm
Machine Net Weight	450kg