

Auger Filler FFS Packing Machine. Model GTL-200-FFSA





Model No. GTL-200-FFSA (Auger Filler)
Application: Flour, Spices, Milk Powder, Cocoa, Coffee Powder, Besan, salt, pepper, spices, etc.

Packaging Range: 200 - 1Kg

TECHNICAL SPECIFICATIONS:

Product application	Powder (Non free flowing Powder), Free flowing Powder	
Sealing Type	Center Seal	
Roll Width	130 mm to 430 mm	
Pouch Size	L (60-35)x W (50-200) mm	
Feeding System	Auger Filler / Volumetric Cup Fille	
Main Motor	1 HP, AC Drive	
Electrical Supply	220 V /AC / Single Phase / 50 HZ OR 440 V /AC Three Phase /50 Hz	
Packing Film	Any Heat Sealable Laminate	
Temperature Controller	PID	
Machine Speed	25-40 Pouch / Min. (Depends upon quantity and product)	
Contact Parts	Food Grande Stainless Steel SS 316 / SS 304	
Compressed Air	6 CFM @ 6 Bar (Depending On Attachments)	
Power Consumption	3 kW	
Net Weight	350 Kgs	
Optional Attachments (At an extra cost)	Batch Cutting Pneumatic Coding Device, Nitrogen Flushing	

SALIENT FEATURES:

Features	Advantages	Benefits
Intermittent Motion Machine	Efficient, effective packing	Savings on wastage
Machine is PLC controlled	Machine is centrally controlled.	System runs in Synchronization
Operator Friendly / Low Maintenance Machine	Easy to Operate / Less Servicing Required	High Run Time / Increased Productivity
Food Grade Stainless steel Contact parts	No rusting	Long Life, Hygienic Packing
Automatic pouch length Change mechanism	Automation	Length can be changed as requirement Less Changeover time, No change Parts
Pneumatic Coding Device (At an extra price)	To Print M.R.P, Month of Packing	Helps In Detecting Manufacturing
Batch Cutting Device	Cuts the Batch at Prefixed length	Ease of secondary packing
Customization (As per products)	Wide dozing system options	Can be used for various products thus -giving full Utility