

## High Density Liquid Filing And Sealing Machine GT6-1(N),GT12-4(N),GT18-6



## High Density Liquid Filing And Sealing Machine(25-210 cans/min)

This machine designs for high-density liquid filling. It equipped 12 rotated filling station with the capacity of up to 1000 g high-density liquid filling. By adopting the Swiss advanced assembling machinery standardization, this machine was designed bu aero-dynamic control sealing with can bottle contactless method, and equipped by touchable screen control pad. This machine is the ideal device for firms like tomato sauce, honey and milk product-wise factory.

This machine designs for high-density liquid filling. It equipped 12 rotated filling station with the capacity of up to 1000 g high-density liquid filling. By adopting the Swiss advanced assembling machinery standardization, this machine was designed bu aero-dynamic control sealing with can bottle contactless method, and equipped by touchable screen control pad. This machine is the ideal device for firms like tomato sauce, honey and milk product-wise factory.

| Technical Parameter |                  |                  |                  |
|---------------------|------------------|------------------|------------------|
| Model:              | GT6-1(N)         | GT12-4(N)        | GT18-6           |
| Capacity            | 25-40cans/min    | 80-180cans/min   | 80-210cans/min   |
| Can Dia             | Ф99mm-153mm      | Ф52.5mm-99mm     | Ф52.5mm-99mm     |
| Can Height          | H89-245mm        | H39-133mm        | H39-133mm        |
| Air Pressure        | 0.5-0.6Mpa       | 0.5-0.6Mpa       | 0.5-0.6Mpa       |
| Power               | 380v 50hz 3KW    | 380v 50hz 5KW    | 380v 50hz 5KW    |
| Overall size        | 2380*1450*2250mm | 3500*1720*2250mm | 3700*1920*2250mm |
| Weight              | 3500kgs          | 4000kgs          | 5000kgs          |