

Horizontal Form Fill Seal Machine HD-180II



Features

- High-speed automatic splicer.
- Electronic cam servo package tractor.
- High reliable PLC control.
- With touch screen to display machine state, operation instruction, the state of breakdown.
- Keyence photoelectric color detector.
- Trio Motion Controllers.
- Camozz pneumatic control components.
- SMC Cylinder.
- Electronic cam servo device for small vehicles.
- Automatic control for material position.
- With safety switch and guard design.
- Connected parts with product made by stainless steel.
- Various of feeding system. (Servo Spiral, Measuring cup, Plunger pump, Gravity Feeder, Hibar Pump, Combination Weigher)

Bag Range

L45*W80mm

Seal Type



Specification

Model	HD-180 II
eeding Station	1
Pouch Format	Twin-Link Flat
Packing Style	3-side seal/4-side seal
Pouch Material	Any Laminated Heat Sealable, ex.PET/CPP, PET/OPP
vlax. Film Diameter	Max. 500 mm
Pouch Size	45*70mm ~ 45*120mm
Pouch Capacity	9 ml
Operating Speed	280ppm
Power Supply	380V 3 Phase 50Hz
Veight	Approx. 1600KG
Machine Size	4700*970*1535 mm

Optional Device

- hanging holeeasy tear