

5 Gallon Bottle Rinsing Filling Capping Machine MJF-series



Functions of 5 Gallon Filling Machine:

1. High safety operation: automatic break protection for power leakage and short circuit;
2. Under-pressure protection: when the pressure of incoming air is $\leq 0.5\text{MPa}$, the filling equipment will automatically stop;
3. Water-shortage protection: when the level of the water tank is lower than that of the liquid switch, the 5 gallon filling machine will stop working automatically.

Remarks:

More functions for our 5 gallon filling machines like hot tank heating washing, bottle external washing, bottle cap washing and human-computer interface control etc. could be provided upon request.

Technical Parameters of MMPL Filling Machines:

1. Micro-computer Bottle Washer/Bottler Filler/Bottle Capper 60BPH

| Model | MJF 60 | MJF 120 | MJF 250 | MJF 450 |
|-----------------------|--|---------------------------------|---------------------------------|----------------------------------|
| Output Bottle/H | 60 | 120 | 250 | 450 |
| Voltage | AC220V/380V \pm 5% 50HZ/60HZ | | | |
| Rated Power | 1.6KW | 4.95KW | 7.16KW | 19.1KW |
| Washing heads | 1 \times 3 | 1 \times 5 | 2 \times 5 | 3 \times 7 |
| Filling heads | 1 \times 1 | 1 \times 1 | 2 \times 1 | 3 \times 1 |
| Capping heads | 1 \times 1 | 1 \times 1 | 2 \times 1 | 1 \times 3 |
| Bottle size | Φ 270 \times 490 \times Φ 56 mm | | | |
| Cap size | Φ 58 \times 40(Tail: L \times W=18 \times 7.5) mm | | | |
| Air pressure | 0.5~0.6MPa | | | |
| N.W. | 195Kg | 300Kg | 395Kg | 950Kg |
| Overall Dimension(MM) | 2710 \times 500 \times 1600 | 3245 \times 500 \times 1600 | 3245 \times 800 \times 1600 | 4390 \times 1100 \times 1760 |