

## Automatic Flow Packing Machine

www.banhing.com.my

Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.

Human-machine operation, convenient and quick parameter setting.

Self diagnosis failure function, clear failure display...

High sensitivity optical electric color mark tracking and digital input cut position which makes the sealing and cutting more accurate..

- Separate PID control to temperature, suitable for various packing materials...
- Stopping the machine in selected position, no sticking to the knife and no waste packing film..
- Simple driving system, reliable working, convenient maintenance..
- All the controls are achieved by software, convenient for function adjusting and upgrading.

Scope of application:

Suitable for regular products like chocolate, moon cakes, biscuit, bread, candy, medicine, daily article, hard wares, tray etc.

## PACKAGING FILM:

Crate Size

> OPP/CPP/PE etc.; must be used in roll, outer diameter ≤300mm, inner diameter is 75mm, the surface of the film must be unknit, no wave on the edge of the film, the color mark must evidently to the colour of the film.

## Specification:~ MODEL CT-320 Type EPM-2023 **Bag Size** (130-350)\*(50-200)\*(3-70)mm(L\*W\*H) Speed 25-180 bag/min Film Thickness 0.04-0.07MM Max Film Width 40MM Max Outer Diameter 300MM **Power Supply** 220V-50Hz Power 5.5KW Total Power Size 4000 x 950 x 1600 (lwh) **Machine Size** Weight 650KG Main Machine 1745(L) x 1100 (W) x 1610 (H) MM

\*Designs and specifications are subject to change for improvement without prior notice.

Tail Machine

## 萬興企業有限公司 BAN HING HOLDING SDN BHD

2560(L) x 370 (W) x 350 (H) MM

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia Tel: +603 4048 1000 Fax:+603 4050 8000 WEB: www.simona.com.my Email: simona@banhing.com