

Auger Filler SP-H2



This type can do dosing and filling work. Due to the special professional design, it is suitable for the fluidic or low-fluidity materials, like milk powder, Albumen powder, rice powder, coffee powder, solid drink, condiment, white sugar, dextrose, food additive, fodder, pharmaceuticals, agriculture pesticide, and so on.

Main features:

- The hopper could be washed easily without tools.
- Servo motor drive screw.
- Stainless steel structure, Contact parts SS304
- Include handwheel of adjustable height.
- Replacing the auger parts, it is suitable for material from super thin powder to granule.

Technical Parameters:

Model	SP-H2	SP-H2L
Hopper	Crosswise Siamese 25L	Lengthways Siamese 51L
Packing Weight	1 – 100g	1 – 200g
Packing Weight	1-10g, $\pm 2-5\%$; 10 – 100g, $\leq \pm 2\%$	$\leq 100g, \leq \pm 2\%$; 100 – 200g, $\leq \pm 1\%$
Filling speed	80 – 200 times per min	80 – 200 times per min
Power supply	3P AC208-415V 50/60Hz	3P AC208-415V 50/60Hz
Total Power	1 Kw	1.7 Kw
Total Weight	160kg	180kg
Overall Dimensions	700×480×750mm	930×430×1000mm