

Candy Pillow Packaging Machine HTL-SF140



Parameters:

1. Full servo motor control, the bag length can be set and cut, only the number of cutters input into the seal can be opened, and the system can realize the split knife operation.
2. Using 7-inch color LCD touch screen integrated control, simple and intuitive operation.
3. Regardless of whether the material supply is continuous or intermittent, under any circumstances, the system can automatically and accurately ensure the uniform material in each packaging film, realize the operation of the material loss without stopping the film, realize the zero empty package, and the packaging material. 0 loss.
4. The material deviation or displacement, the cutter stops, and the cutter automatically resumes operation after the material is discharged.
5. The device built-in without stopping the automatic film, saving costs.
6. Intelligent modular temperature control temperature control is more accurate.
7. The color mark tracking accuracy is high.
8. The drive is simple, reliable, easy to maintain and maintain, has not been exposed to the installation, maintenance, operation of the equipment, can be mastered in 5 minutes.
9. The whole machine is equipped with multiple security protection measures.

Specifications:

Model	HTL-SF140				
Packing tim width Max(m)	150	280	350	450	550
Bag engh(mm)	50-500	50-500	50-500	50-500	50-500
Bag wdth(mm)	30-60	50-140	50-170	50-210	50-260
Max product eghtm)	5-40	5-60	5-60	5-70	5-100
Role danertm	300	300	300	300	300
Packing peedbags/min)	50-350	50-350	50-350	50-350	50-350
Votago	220/380V,50Hz	220/380V,50Hz	220/380V,50Hz	220/380V,50Hz	220/380V,50Hz
Powerteo)	3	3	3	3	3
Dimendion(mm)	4000*950*1450	4000*950*1450	4000*950*1450	4000*950*1450	4000*950*1450