



ZH-V620 Automatic Granule Packing Machine



Feature:

1. Adopting PLC from Japan or Germany to make machine run stable. Touch screen from Tai Wan to make operation easy.
2. Sophisticated design on electronic and pneumatic control system makes the machine with high level of precision, reliability and stability.
3. Double-belt pulling with servo of high precise positioning makes film transporting system stable, servo motor from Siemens or Panasonic.
4. Perfect alarm system to make problem solved quickly.
5. High Accuracy in bag length and positioning.
6. Adopting intellectual temperature controller, the temperature is controlled to ensure neat sealing.
7. Machine can make pillow bag and standing bag (gusseted bag) according to customer's requirements. Machine also can make bag with punching hole & linked bag from 5-12bags and so on.
8. Working with weighing or filling machines such as multihead weigher, volumetric cup filler, auger filler or feeding conveyor, process of weighing, bag making, filling, date printing, charging (exhausting), sealing, counting and delivering finished product can be completed automatically.

Application:

It is suitable for packing grain material, sheet material, strip material and abnormality material which such as candy, sunflower seeds, peanut, nuts, beans, potato chips, popcorn, almond, dry fruit, vegetable salad, frozen food, jelly, biscuit, chocolate, etc.

Technical Specification:

Model	ZH-V620
Packing speed	25-50Bags/Min
Bag size(mm)	W:90-250mm L:80-350mm
Bag making mode	Pillow bag, standing bag (gusseted), Punching bag Connecting bag
Max film width (mm)	620
Thickness of film (mm)	0.04-0.09mm
Air consumption	0.5 m ³ /min 0.8MPa
Packing Material	laminated film such as POPP/CPP, POPP/ VMCPP, BOPP/PE, PET/ AL/PE ,NY/PE, PET/ PET.
Power Parameter	220V50/60Hz 4KW
Dimension(mm)	1620(L)×1340(W)×2100(H)
Gross Weight(kg)	700