

PTYG-4B6B8B Rotary Capping Machine



With 4 mechanical hands, the model is used for multi-geometry containers. It dispatches caps at high speed without any cap reversed. Cap supply system and mechanical hands work together in phase. When the cap is tightened, bottle and cap stand still relatively, and the clutch separates immediately so that cap and bottle are not apt to be damaged.

FEATURES

- ✓ Modular manufacturing, easy to assemble or disassemble, and easy to maintain. Screw the cap at high speed and efficiency is high, Safe and reliable.
- ✓ It is equipped with aluminum foil and bend cap tripping device to ensure the quality of products.
- ✓ Can be equipped with independent control cabinet, simple operation, safe and reliable.
- ✓ It is especially suitable for capping round caps like edible oil, sauce, lotion, cream, lubricating oil bottles.

TECHNICAL PARAMETERS

Type	PTYG-4B	PTYG-6B	PTYG-8B
Capping heads	4	6	8
Production speed (bottles/hour)	≤4500 bph	≤6000 bph	≤8000 bph
Suitable bottles	customized		
Cap size	Φ20*10-Φ80*35		
Power	2.5KW	3KW	3KW
Power source	220/380V 50/60Hz		
Air source	0.6Mpa		
Dimension(mm)	2400×1400×2200	2400×1400×2200	2400×1400×2200