

KD-260/350/450 Flow Wrap Machine



Suitable for biscuits, packaging of all kinds of objects with regular solid state, such, as bread, speed wheaten food, moon, cake, candy, medicines, daily necessities, five metals part, paper carton or the tray, etc.

Featrues:

- Compact structure, stable function and simple operation.
- Double frequency converter controller, length of package will cut immediately once setting, adjustment needless, saving time and film.
- It adopts imported electric appliance, touch man machine interface, convenient parameter setting.
- Self-checking function, trouble can be read easily. High sensor photoelectric color chart tracking, make the cutting position more correctly.
- Dependant temperature PID controlling suitable for various materials of packaging membrane. Position stop function, no adhesive and no waste of membrane.
- Clean rotation system, more reliable operation and more convenient maintenance.
- All the controlling operates by the software, convenience for function adjustment and technical up grading.

Technical Data

Model	KD-260	KD-350	KD450
Max.film width	260mm	350mm	450mm
Max packaging capacity(according to its material to fix)	50-220p/min	50-220p/min	50-220p/min
Suitable film thickness	0.03-0.06mm	0.03-0.06mm	0.03-0.06mm
Length of bags	60-330mm	60-330mm	60-330mm
Packaging with	30-110mm	30-150mm	30-180mm
Packaging height	5-40mm	5-70mm	5-80mm
Intensity of Sealing	≥15	≥15	≥15
Total power	2.7Kw 220V 50hz	2.7Kw 220V 50hz	2.7Kw 220V 50hz
Overall dimensions (LxWxH)	4000x920x1500	4000x920x1500	4000x1200x1500
Weight	500kg	550kg	680kg