



WU-HSING ELECTRONICS CO., LTD.  
since 1991

## *WSY-100/800/900 Desktop Horizontally*



WU-HSING's desktop band sealing machines WSY-800/100/900 series, metal body with powder coating, horizontal model (the bag is placed flat on the conveyor for operation.)

Temperature control, need warm up time: 10 minutes, must maintain the set temperature.

Suitable for dry and solid products.

Total conveyor load: <1 KG (Not one package weight), suitable for small and light packages.

The conveyor can be adjusted up and down about 5cm, front and back 4cm.

Suitable for various materials. The combination of temperature and speed can easily complete the sealing and packaging operation.

800 model- digital Control panel, 500W of heater, lighter weight: 35kgs

100 model- digital Control panel, 600W of heater, ideal for sterilization pouch using

900 model-buttons operation, 350W of heater, weight: 48 kgs.

### **Application**

- Food, chemicals, hardware parts, pharmacy ...

**Features:**

- Conveyor loading weight: <1KG
- Conveyor width: 150mm /200mm
- Adjustable speed: 1-10M/per minute.
- Sealing width: 5mm or 10mm depends on materials (PE: 5mm, Nylon, Alum materials: 10mm)
- Applications for food, chemistry, hardware parts packaging and Tyvek sterilization pouch.
- If >2KG, please use WSY-901; if liquid or powder, please select WSY-904, 905

**Specification**

Specification	WSY-100	WSY-800	WSY-900
Voltage	110V/220V/240V		
Conveyor width	150mm	150mm	200mm
Loading weight of Conveyor	1 KG		
Sealing Width	10 mm	5mm or 10mm	5mm or 10mm
Temp. Range	50-299°C	50-230°C	50-230°C
Dimension	850*510*350 mm	850*510*350 mm	1050*520*390mm
Weight	35 KG	35 KG	48 KG