

Flat Surface Top Labeling Machine SBM-620



The automatic flat labeling machine is the new generation of packaging equipment. It is special designed based on the automatic labeling machine technology and technical requirements. Can make the adhesive labels stick on the bottle surface smooth and tidy. Labeling process is stable and reliable, and labeling position can reach the ideal requirements.

The automatic flat labeling machine belongs to the electromechanical integration products with reasonable structure. It is used to rolling the adhesive label on the round bottles automatically, when there is lack of bottle, the control system will stop offering the labels, which can avoid the label paper waste effectively, and can adjustment stepless according to the scale of the bottle and the label characteristics.

Features

- Suitable for labeling on the flat surface of various products.
- Controlled by the stepping motor, adopts Keyence fiber made in Japan to ensure the labeling accurate and in high quality.
- Dispense special training, the workers can operate and maintenance the machine easily after the simple guidance. The electrical components are all standardization parts, when something is broken, you can purchase them anywhere, the daily maintenance and management are also convenient.
- The whole machine adopts SUS304 stainless steel and T6 aluminum alloy materials, parts and components adopt standardized design, fully comply with GMP environmental requirement.

Main Products

Liquid Filling Production Line: Oral Liquid Filling Line; Eyedrop Filling Line; Syrup Filling Line; Cosmetics Filling Line; Medicinal Liquor; Pesticides Filling Line; Special Bottled Filling Line

Table and Capsule Packaging Line: Counting and Packaging Line for Tablet, Capsule, Solid Pills, Cachou etc

Production Line Consists of: Bottle Unscrambler-Bottle Washing-Filling-Capping-Labeling(Shrink Sleeve Labeling Machine)-Boxing Machine

Specialized in various kinds of non-standard automation equipments.

Technical Info

Model	SBM-620
Voltage	AC110V;50/60HZ
Power	180W
Speed	0-240 pcs per minute (according to the size of the product and the label)
Accuracy	±1mm (according to the surface evenness of the product)
Suitable range of the products	Length 30mm-300mm, Width 30-260mm
Suitable range of the labels	Length 20mm-300mm, Width 15mm-120mm
Specification of the label roll	Outer diameter: 300mm, Inside diameter: 76mm
Overall dimensions	2000mm×650mm×1300mm(L×W×H)
Weight	250kg