



# CLGFR series Measuring Cup Type Fruit Pulp Beverage Four in One Filling Machine



This production line is a specialized equipment for cleaning, filling, and sealing plastic barrels. As the production line has introduced advanced and mature technologies from European countries, it has the advantages of high degree of automation, strong adaptability, easy operation, good safety performance and so on, and its progressiveness is in the leading position among similar products in the same industry in China.

This equipment is suitable for automatic filling of 3-6L pure water, suitable for various shaped bottles. The filling volume can be continuously adjusted, and each filling valve can be fine tuned.

## Technical Parameters

| 主要技术参数 Main Technical parameters                    |                                        |                          |                          |                          |                          |                          |
|-----------------------------------------------------|----------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| 型号<br>Model                                         | XGF4-4-1                               | XGF8-8-1                 | XGF12-12-1               | XGF12-12-4               | XGF16-16-4               | XGF20-20-6               |
| 冲洗、灌装、旋盖头数<br>Heads of washing, filling, capping    | 4-4-1                                  | 8-8-1                    | 12-12-1                  | 12-12-4                  | 16-16-4                  | 20-20-6                  |
| 生产能力(5000ml)瓶/时<br>Production capacity(bottle/hour) | 600-800                                | 1200-1500                | 1800-2000                | 3000-3500                | 4000-4500                | 5000-6000                |
| 适用瓶型规格(mm)<br>Suitable bottle diameter(mm)          | $\phi=110-200$ H=170-380(5000-10000ml) |                          |                          |                          |                          |                          |
| 喷冲压力(kg/cm <sup>2</sup> )<br>Spraying pressure      | 2~3                                    |                          |                          |                          |                          |                          |
| 电机功率(kw)<br>Motor power                             | 主电机<br>(Main motor)3.0kw               | 主电机<br>(Main motor)3.0kw | 主电机<br>(Main motor)3.7kw | 主电机<br>(Main motor)5.0kw | 主电机<br>(Main motor)6.5kw | 主电机<br>(Main motor)9.0kw |
| 外形尺寸(mm)<br>overall dimension(L×W×H)                | 4200×1400×2500                         | 6100×1400×2500           | 8800×1400×2500           | 3100×2100×2550           | 3800×2300×2800           | 4500×2800×2900           |
| 重量(kg)<br>Weight                                    | 2500                                   | 3500                     | 4500                     | 4800                     | 5500                     | 7500                     |