



FL-5545T Pneumatic L-Bar Sealer Packing Machine



Suitable for the packing demands of the mass production in industries such like electronics, hardware, plastic, software, food, printing, pharmaceuticals, floors and other construction materials.

Applicable films: PVC/POF.

Pneumatic L Bar Sealer Technical Features:

- Teflon coated sealing wires in glass-fiber slots, making the seam straight, closed and unburnt.
- Miscalculation and overheating protection devices can effectively protect the products and the operator.
- Tailored perforators to fully evacuate the air from the film bags.
- FL-5545TB/7555TB cut and seal by cylinder, saving physical strength while improving the efficiency.

Shrink Tunnel Features:

- Stainless heating tubes and strong blowing motor ensure high heating efficiency, large air volume and uniform air circulation.
- Solid metal rods wrapped by heat-resistance silicone tubes make the Conveyor rollers strong and resilient.

Technical Parameters

Model	FL-5545T
Machine Dimensions (mm)	1569×710×1060
Max packing size L+H(mm) H<200	≤500
Max Packing Size W+H(mm) H<200	≤400
Max Sealing Size (mm)	550×450
Packing speed (pcs/h)	800-1200
Conveyor speed (m/min)	
N.W. (kg)	150
Power (kw)	1.2
Power supply	1PH 110V/220V 50/60Hz
Applicable Film	POF/PVC